



NetVanta 2300

Mid-Range VPN Gateway and Firewall

Product Features

- IPsec VPN tunneling with DES/3DES encryption
- Internet Key Exchange (IKE) for user authentication
- Stateful inspection firewall security
- DMZ Port for public server access
- Hardware Encryption Accelerator
- Up to 100 private encryption tunnels
- Logging and alerts
- Web-based management
- 10/100 BaseT Ethernet interfaces for flexible connectivity



The ADTRAN NetVanta™ 2300 is a mid-range IPsec compliant gateway providing all the necessary components required to secure an integrated VPN solution. As a branch office or mid-size host security gateway, the NetVanta 2300 provides several key security features such as IPsec VPN tunneling with DES or 3DES encryption, stateful inspection firewall, and IKE for user authentication supporting public/private keys or digital certificates. In addition, it also offers a DMZ port for public server access, a hardware encryption accelerator for faster encryption throughput and up to 100 simultaneous VPN tunnels.

Security: On a public infrastructure like the Internet, security is of the utmost importance. The NetVanta 2300 protects the corporate network against attacks with a built-in firewall and provides data security through encryption, authentication and key exchange. The NetVanta 2300 employs a stateful inspection firewall that protects an organization's network from common cyber attacks including TCP syn-flooding, IP spoofing, ICMP redirect, land attacks, ping-of-death, and IP reassembly problems. The NetVanta 2300 also encrypts the data being sent out onto the network, using either the DES (Data Encryption Standard) or 3DES encryption algorithms. Data integrity is ensured using MD5 or SHA1 as it is transported across the public infrastructure. In addition, Internet Key Exchange (IKE) can be used for user authentication supporting public/private keys or digital certificates, assuring that the proper VPN tunnel is established and that the tunnel has not been redirected or compromised.

VPN Tunneling: NetVanta 2300 is an IPsec compliant device that supports both ESP and AH protocols and provides secure communication over potentially unsecure network components. As a security gateway, the NetVanta 2300 can support up to 100 private encryption communication tunnels through the Internet from remote locations. The NetVanta 2300 can also hide IP addresses from the external world by performing Network Address Translation (NAT).

Web-based Management: Configuring a remote NetVanta 2300 can easily be managed using a standard web browser. NetVanta 2300 has built-in alert and logging mechanisms for messaging and mail services. This enables the unit to warn administrators about activities that are going on in the network by logging them into a SYSLOG server or sending an email to the administrator.

The NetVanta 2300 offers guaranteed interoperability with ADTRAN's complete line of NetVanta 2000 Series of VPN/Security gateways: NetVanta 2050 for work-at-home telecommuters, NetVanta 2100 for small office connectivity, NetVanta 2400 for larger corporate host applications, and the software implemented, NetVanta VPN Client. Together the NetVanta 2000 Series offers the most robust features and functions to address a wide range of enterprise VPN needs.



ADTRAN, Inc.

Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax
256 963-8200 fax back

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy

877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

Post-Sales

Technical Support

888 423-8726
support@adtran.com
www.adtran.com/support

ACES Installation & Maintenance Service

888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries

256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

For the regional office nearest you, visit:

www.adtran.com/where2buy



I.S. EN ISO 9001
ADTRAN is a
ISO 9001 registered company.



TL 9000

ADTRAN is a
TL 9000 registered company.

Printed in the U.S.A.

61200366L1-8B July 2002

©2002 ADTRAN, Inc. All rights reserved.

NetVanta 2300

Mid-Range VPN Gateway and Firewall

Product Specifications

Physical Interface

- **WAN:** RJ-45 10/100 Auto-Sensing Ethernet interface
- **LAN:** RJ-45 10/100 Auto-Sensing Ethernet interface
- **DMZ:** RJ-45 10/100 Auto-Sensing Ethernet interface
- **Serial Port:** RS-232 for off-net configuration

Virtual Private Network (VPN)

Hash Algorithms

- MD5-HMAC 128-bit authentication algorithm
- SHA1-HMAC 160-bit authentication algorithm

Encryption

- DES-CBC 56-bit encryption
- 3DES-CBC 168-bit encryption

Diffie Hellman Group Support

- Group 1: MODP 768
- Group 2: MODP 1024

Authentication Mechanisms

- Preshared keys
- **X.509 Certificate Support:**
RSA Signatures, DSS Signatures

Key Management

- IKE (ISAKMP/Oakley)

IPSec Mode

- Tunnel

IKE Modes

- Main
- Aggressive
- Quick

Firewall

- Stateful inspection firewall
- Application content filtering
- Cyber assault protection
- HTTP Relay

Diagnostics

Front Panel Status LEDs

- Power – status
- VPN – status, transmit, receive
- LAN – transmit, receive
- WAN – transmit, receive

Routing

- TCP/IP
- Static Routes
- RIP V1 & RIP V2

Administration

- Web-based management
- SYSLOG logging in WELF format
- Email alerts (SMTP)
- User and group access control policies based on time-of-day
- User accounting policy statistics

DHCP

- Server (to manage IP addresses on local network)
- Client (to acquire the WAN-side IP address from service provider)

PPPoE

- Client (to acquire the WAN-side IP address from service provider)

Address Translation

- Basic NAT (1:1)
- NAT (Many:1)
- Reverse NAT (translation of an inbound session's destination IP address)

Environment

Operating Temperature

- 0° to 50 °C (32° to 122 °F)

Storage Temperature

- -20° to 70 °C (-4° to 158 °F)

Relative Humidity

- Up to 95%, non-condensing

Physical

Size: 1.25" H, 17.25" W, 7.75" D

Weight: 7 lbs (shipping weight)

Power: 100 - 250 vAC, 50/60 Hz

Agency Approvals


- FCC Part 15 (Class B)
- UL and Canadian UL (CUL), IEC/EN, CSA

Product Includes

- User manual
- AC power cord
- Rackmount brackets

Ordering Information

Equipment	Part #
NetVanta 2300	1200366L1



Specifications subject to change without notice. ADTRAN and NetVanta are trademarks of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.